


The machine room must be dry and well ventilated. The room temperature must be 10 °C - 30 °C.

Main switch (Fa. Lödige)
Elec. fuse (by others)

Call button panel
Signal lights



Option 1
Machine room
min.2000x2000
min.2100mm hoch

Technicale Data:
The technical data listed here are examples. All data correspond to the information from the planning guide for the car lift Carrico & Traffico. Further information can be found there.

Example lift	3500 kg	(can be reduced on request, technical clarification required)
Payload:	0,3 m/s	
Lifting speed:	max. 2.100 kg	
Axle load:	2.800 mm	
Cabin width:	5.800 mm	
Cabin depth:	2.100 mm	
Cabin height:	6.000 mm	
Lifting height:	1.250 mm	
Pit:	3.600 mm	
Shaft width:	6.600 mm	
Shaft depth:	3.500 mm	
Headroom:	2	
Number of stops:	2, through car loading	
Entrances:	Option 1 of the planning guide	
Machine room:		

The technical data can be adapted to your wishes after consultation with you.

Notice:
This sample shaft drawing of the CARRICO® and TRAFFICO® car lift serves only as information material and does not replace the official shaft drawing. An official shaft drawing of the elevator is required for the final and detailed building planning. If necessary and in consultation with you, our sales department and our construction team will adapt this to your building project.

COPYRIGHT & DISCLAIMER

The content of these drawing template — particularly text and graphics — are protected by copyright. Unless indicated otherwise, copyright is held by Lödige Fördertechnik GmbH. The content of this document must not be published without the express consent of Lödige Fördertechnik GmbH. We reserve the right to make technical changes to the drawing template for the CARRICO® and TRAFFICO® car lift.