

Technical Data:

The technical data listed here are exemplary and serve as customer information.

Example lift

Payload:	2.000 kg	Headroom:	2.650 mm
Lifting speed:	0,15 m/s	Number of stops:	2
Axel load:	max. 1.200 kg	Entrances:	2, above each other (one side loading)
Cabin width:	1.400 mm	Control box:	In the second floor fixed on the shaft
Cabin depth:	2.000 mm	Rated power:	7,5 kW
Cabin-/door height:	2.000 mm	Nominal current:	15 A
Lifting height:	3.750 mm	Rated fuse current:	37,5 A with frequency converter
Pit:	90 mm	Operation methode:	S3/S6-60%
Shaft width:	1.770 mm	Passengers:	Are allowed
Shaft depth:	2.180 mm		


The technical data can be adapted to your wishes after consultation with you.

Notice:

This sample shaft drawing of the goods lift ESCORTA® serves only as information material and does not replace the official shaft drawing. An official shaft drawing of the elevator is required for the final and detailed building planning. If necessary and in consultation with you, our sales department and our construction team will adapt this to your building project.

COPYRIGHT & DISCLAIMER

The content of these drawing template — particularly text and graphics — are protected by copyright. Unless indicated otherwise, copyright is held by Lödige Fördertechnik GmbH. The content of this document must not be published without the express consent of Lödige Fördertechnik GmbH. We reserve the right to make technical changes to the drawing template for the goods lift ESCORTA®.

Goods lift ESCORTA after MD 2006/42/EC			
Payload: 2.000 kg, Passengers allowed			
Lifting speed 0,15 m/s			
Sample drawing			
ESCORTA			
Date:		Scale:	
27.03.2020		1:20	
Name:			
HAASE			
Barb.:			
Gepr.:			
		Lodge (United Kingdom) Ltd. Laxton House Eversley Way TW20 8RY Egham, Surrey United Kingdom	
Escorta No.:		ESCORTA	
Zachow Nr.:		SAMPLE	
"Copyright reserved. Violation will be prosecuted."			